




## JT-T2460




### 2.4GHZ Active RFID Tag

The JT-T2460 active rfid tag can be identified from a long distance and is safer to use. It is elegant and beautiful in appearance, compact and exquisite, easy to install and support reliable and stable work for more than 3 years. The surface of the tag can be customized with logos, barcodes, etc. printed on it. Suitable for large-scale valuable asset management, animal management, vehicle management, personnel management and other application scenarios.

# SPECIFICATIONS

## PARAMETERS

Working frequency	2.4 GHz~2.45 GHz
Transmit time interval	1s/time
Reading range	0~150m (relate to reader and environment)
Identification method	Active emission + omnidirectional 360 reading
Transmit power	-13dBm ~ +7dBm
Modulation	GFSK
Communication rate	250Kbps/1Mbps(default)/2Mbps
Low battery alarm	Support
Battery	CR2450(560mAh)(not replaceable)
Working voltage	DC 3V
Working current	≤18μA
Stand-by current	≤6uA
Working temp.	-20℃~+60℃
Storage temp.	-40℃~+125℃
Storage humidity	5%~95%RH no condensation
Material	ABS
Dimension	41*41*20mm
Weight	13.9g



## Shenzhen Jietong Technology Co.,Ltd

Address : 12/F, Building A, No. 6, Shibei Road, Shiyan Street, Bao'an District, Shenzhen, Guangdong, China 518108

Email : marketing@jtspeedwork.com

Website : www.jtspeedwork.com