




JT-HC706



2.4GHz RFID Handheld Reader

The device uses Android 12.0 system, quad-core high-speed processor, 3GB RAM, 32GB ROM; supports 128GB TF card expansion, large storage capacity, fast running speed, stable performance. It can easily handle various task instructions and support smooth processing of multiple tasks, which is the best guarantee for mobile information processing.

Shenzhen Jietong Technology Co.,Ltd

Address : 12/F,Building A, No. 6,Shiben Road,Shiyan Street,Bao'an District,Shenzhen,Guangdong,China-518108

Email : marketing@jtspeedwork.com

Website : www.jtspeedwork.com

SPECIFICATIONS

PERFORMANCE PARAMETERS	
Working frequency	2.45GHz
Reading range	0-100 meters
CPU	MTK 6762-8 core
RAM+ROM	3+32GB/4+64GB(optional)
Data Communication	4G:TD-LTEBand38/39/40/41FDD-LTEBand1,2,3,4,7,17,20 3G:WCDMA(850/1900/2100MHz); 2G:GSM/GPRS/Edge(850/900/1800/1900MHz)
WiFi	WIFI 802.11 b/g/n/a/ac Frequency 2.4G+5G Dual-band WIFI
Bluetooth	Bluetooth4.0
2G/3G/4G	CMCC 4M : LTE B1,B3,B5,B7,B8,B20,B38,B39,B40,B41 ; WCDMA 1/2/5/8; GSM 2/3/5/8
NFC(OPTIONAL)	
Working frequency	13.56MHz
Protocol	ISO 14443A&15693
Reading range	2-5cm
PARAMETERS	
Operating system	Android 12.0
Display	5.72-inch IPS high-definition screen, resolution 1440*720
Touch screen	Multi-touch, Corning grade 3 tempered glass screen
Expansion slots	1 sim card slot, 2 PSAM card slots
Camera	5-megapixel front camera, 13-megapixel rear camera, autofocus with flash
Flashlight	Low power LED lighting for emergency use
GPS	Navigation built-in GPS global positioning system, error range $\pm 5m$
Battery capacity	3.7V/4000mAh
Battery life	About 8 hours (standby time > 300h)
Size	178*83*17mm
Weight	280g
Operating Temp.	-20° C~50° C
Storage Temp.	-20° C~70° C
Humidity	5-95% non-condensing (+25° C)
Protection level	IP65